



GETAC V110 RUGGED CONVERTIBLE TABLET

<i>Model name</i>	Getac V110 Rugged Convertible Tablet
<i>Operating system</i>	SDC 5.X Windows 10 Pro 64-bit with Office Suite (default)
<i>Processor</i>	Intel® Core™ i5-6200U 2.3Ghz (2.8Ghz turbo boost) 5GT/s 3MB cache, 64-bit dual-core processor, supports both Intel VT-X and VT-D
<i>Chipset</i>	System equivalent to Intel HM75 chipset
<i>Memory</i>	4GB DDR4-2133 SDRAM installed, up to 8GB
<i>Display</i>	11.6" HD (1366x768) 800 NITS sunlight readable display with integrated multi-point touchscreen
<i>Hard drive</i>	128GB M.2 SATA3.0 solid state drive, self-encrypting & FIPS 140-2 compliant
<i>Audio</i>	Integrated HD audio controller with built-in speakers
<i>Graphics</i>	Integrated Intel HD 520 graphics up to 1.7GB dynamic shared VRAM; Digital video HDMI port; HDMI-to-VGA adapter is included
<i>Communications</i>	Integrated 10/100/1000 Gigabit Ethernet; Integrated Intel Dual Band Wireless-AC 8260 802.11A/B/G/N/AC (Controllable in BIOS)
<i>I/O ports & connectors (all ports covered & sealed)</i>	2x USB 3.0 ports, 1x USB 2.0 port, 1x audio-in/audio-out combo port, 1x RJ-45 port, 1x RS-232 serial port, 1x HDMI port
<i>Expansion slots</i>	1x ExpressCard/54 slot (sealed with cover), 1x docking connector (sealed with cover)
<i>CAC reader</i>	1x integrated FIPS 201 complaint CAC reader (fully-sealed when door is closed)
<i>Input device & keyboard</i>	Integrated US rubber backlight keyboard, 88 keys; Integrated touchpad with 2 buttons, stylus pen tethered to tablet
<i>Power</i>	65W AC adapter dual voltage (100-240V 50/60Hz), autosensing; Dual battery configuration: 2x hot swappable 2100mAh batteries; Total 13.6 hours combined battery life for normal usage
<i>Security</i>	TCG Certified TPM 2.0 Module

<i>Rugged</i>	Magnesium alloy case with integrated carry handle, features a stealth-mode/black-out button to instantly extinguish all device lights including the screen
<i>Dimensions & Weight</i>	11.7" x 8.78" x 1.26" / 299mm x 223mm x 34mm; 4.39lb / 1.99kg (including dual battery configuration)
<i>Environmental & Regulatory</i>	EPEAT Gold Rating, RoHS Compliant, NIST SP800-147 BIOS, TAA
<i>Warranty</i>	3-year mail-back with hard drive retention; NCS pays shipping both ways, accidental damage protection; battery replacement warranty

<i>ETOOLS-2016 Available Options</i>	
<i>Hard drive (storage)</i>	Upgrade to 256GB solid state drive, self-encrypting, FIPS 140-2 compliant
<i>RAM memory</i>	Upgrade RAM to 8GB
<i>Battery upgrade</i>	Add 2x Getac V110 2100mAh hot-swappable battery packs
<i>Dual battery charger</i>	Add Getac V110 dual bay external primary battery charger with AC adapter
<i>Docking solution</i>	Add V110 office docking station (w/ AC adapter) which includes 1x USB 3.0 port, 3x USB 2.0 ports, 1x RJ-45 port, 1x audio-in, 1x audio-out, 1x VGA port, 1x HDMI port, 2x RS-232 serial ports
<i>Sealed screwheads</i>	Add heat-cured self-leveling sealant to all exposed screw heads (FOD)
<i>Broadband</i>	Add Gobi/4G mobile broadband wireless module
<i>Wireless</i>	Add 100MW booster module (can't have Gobi/4G module simultaneously)
<i>Webcam</i>	Add integrated front and rear webcam
<i>Dock - vehicle</i>	Add V110 vehicle mount
<i>Mouse</i>	Add USB 2-button mouse
<i>Keyboard</i>	Add USB 104-key (non-CAC reader) keyboard
<i>Warranty</i>	Upgrade to 4-year mail-in/mail-back warranty with hard drive retention, accidental damage protection, and battery replacement



7669 Limestone Drive
Gainesville, VA 20155
Toll-Free: 1 (888) RING-NCS
Voice: (703) 743-8500 / Fax: (703) 621-1701
ncst.com

Actual functionality may be limited to other factors, including type, number and capabilities of Optional modules incorporated. NCS may make changes to product specifications at any time and without notice. The information in this document is for informational use only, is subject to change without notice. NCS assumes no responsibility or liability for any errors or inaccuracies that may appear. All names are provided for informational use only. Other brands and names may be claimed as property of their respective owners.

ETOOL-RCT-04-092616